

4" STAINLESS STEEL SERIES

Performance Table



Pump model	Motor kW	lps m³/h	0 0	0.11 0.4	0.16 0.6	0.22 0.8	0.27 1	0.33 1.2	0.38 1.4	0.44 1.6	0.5 1.8	0.55 2	0.61 2.2	0.72 2.5	0.83 3	0.97 3.5	1.11 4	1.25 4.5	1.39 5	1.66 6	1.94 7	2.22 8	2.5 9	2.78 10	3.05 11	3.33 12	3.89 14	4.44 16	5 18	OUTLET SIZE IN INCHES	NET WEIGHT in kg		
S4S-1/09	0.37	Head in meters	50	45	41	38	32	26.5	20	12																				1¼	4.4		
S4S-1/14	0.37		80	70.5	65	58	49	39	29	18																				1¼	6.1		
S4S-1/18	0.55		105	94	88	79.5	70	59.5	47	33																				1¼	7.3		
S4S-1/21	0.55		125	116.5	108.5	99	85	69.5	53	39																				1¼	8.4		
S4S-1/28	0.75		165	148	135	122.5	107.5	90	69	47																				1¼	10.7		
S4S-1/36	1.1		198	182	165	145	123	102	80	54																				1¼	16.9		
S4S-1/42	1.1		230	211	190	165	140	116	89	60																				1¼	18.7		
S4S-1/50	1.5		280	250	226	199	170	140	106	70																				1¼	21.4		
S4S-1/57	1.5		320	284	253	221	189	155	120	82																				1¼	22.8		
S4S-2/06	0.37	Head in meters	35	27	28	27	26.5	25	25	24	23	20	17	8																	1¼	4.1	
S4S-2/09	0.37		54	50	49	48	45	43	40	37	35	30	25	19																	1¼	4.8	
S4S-2/13	0.55		76	74	72	70	68	65	60	53	48	42	36	27																	1¼	5.7	
S4S-2/15	0.55		90	86	82	80	78	75	70	65	60	57	48	38																	1¼	6.1	
S4S-2/18	0.75		120	118	115	110	102	98	92	87	80	72	63	50																	1¼	6.8	
S4S-2/23	1.1		145	143	140	135	128	123	113	102	93	82	71	57																	1¼	8	
S4S-2/28	1.5		180	175	172	166	160	150	142	132	121	110	98	77																	1¼	9.1	
S4S-2/33	1.5		215	205	199	195	183	175	165	152	140	124	108	82																	1¼	10.2	
S4S-2/40	2.2		249	240	232	225	218	206	195	177	165	144	127	92																	1¼	12.5	
S4S-2/48	2.2		285	276	272	262	254	240	227	212	195	174	148	100																	1¼	15.2	
S4S-2/55	3		335	320	306	295	282	243	250	227	209	183	158	110																	1¼	17.5	
S4S-2/65	3		405	385	375	360	342	298	301	280	257	228	196	138																	1¼	22.3	
S4S-2/75	4		460	445	435	424	403	380	363	330	305	272	235	164																	1¼	26.8	
S4S-2/90	4			535	520	513	495	473	424	421	390	358	319	276	198																1¼	33.2	
S4S-3/06	0.37	Head in meters	36									32	32	31	30	28	22	17	10												1¼	2.3	
S4S-3/09	0.55		54									52	50	49	48	42	35	27	15												1¼	3.4	
S4S-3/12	0.75		75									68	65	63	60	54	45	33	20												1¼	4.2	
S4S-3/15	1.1		98									90	86	84	80	72	60	45	28												1¼	5	
S4S-3/18	1.1		110									115	102	100	95	86	73	52	34												1¼	5.6	
S4S-3/22	1.5		145									134	130	125	120	105	88	65	40												1¼	6.6	
S4S-3/25	1.5		168									152	148	142	134	117	98.5	74	45												1¼	7.3	
S4S-3/29	2.2		190									178	170	165	159	140	117	89.5	50												1¼	8.2	
S4S-3/33	2.2		216									200	195	190	181	161	130	95	57												1¼	13.2	
S4S-3/39	3		250									232	225	213	209	186	155	118	66												1¼	14.2	
S4S-3/45	3		280									255	249	240	233	210	180	137	81												1¼	17.3	
S4S-3/52	4		330									296	290	285	272	244	206	162	103												1¼	19.2	
S4S-3/60	4			384								337	328	317	304	274	228	180	110												1¼	22.2	
S4S-5/04	0.37	Head in meters	28										26	25	25	22.5	22	20	20	17	12	5	4								1¼	2.8	
S4S-5/06	0.55		39										36	35	35	32	30	28	25	22	17	10	8								1¼	3.5	
S4S-5/08	0.75		46										42.5	42	42	40	40	37	35	32	23	15	10								1¼	4	
S4S-5/12	1.1		75										71	70	69	65	61	57	52	48	38	24	18								1¼	5.4	
S4S-5/17	1.5		108										94	92	90	88	84	80	74	68	51	33	25								1¼	6.9	
S4S-5/21	2.2		138										121	120	118	112	106	99	92	84	65	42	34								1¼	8	
S4S-5/25	2.2		162										143	140	138	131	126	119	110	102	77	53	40								1¼	9.1	
S4S-5/33	3		202										179	178	172	165	158	147	139	128	100	68	48								1¼	13.9	
S4S-5/38	4		241										215	211	208	198	189	177	166	152	119	81	60								1¼	15.3	
S4S-5/44	4		280										244	240	234	223	210	199	186	170	134	92	70								1¼	17.5	
S4S-5/52	5.5		324										281	278	270	258	244	230	216	199	156	108	80								1¼	20.5	
S4S-5/60	5.5		360										322	318	312	300	288	262	255	236	190	130	99								1¼	22.2	
S4S-5/75	7.5			487									427	419	410	392	374	352	330	302	237	168	134		</								

4" SILVER LINE SERIES

Performance Table



Pump model	Motor kW	lps m³/h	0 0	0.20 0.75	0.27 1	0.34 1.25	0.41 1.5	0.48 1.75	0.55 2	0.69 2.5	0.83 3	0.97 3.5	1.1 4	1.25 5	1.66 6	1.94 7	2.22 8	2.78 10	3.33 12	3.89 14	4.44 16	5 18	5.56 20	6.11 22	OUTLET SIZE IN INCHES	NET WEIGHT in kg	
S4P-1E/08	0.37	Head in meters	54	46	42	38	32	24	15																1¼	3.3	
S4P-1E/13	0.55		89	78	75	70	61	50	38																1¼	4.2	
S4P-1E/17	0.75		116	101	94	84	73	59	43																1¼	5	
S4P-1E/18	0.75		122	111	102	93	81	67	49																1¼	5.3	
S4P-1E/25	1.1		166	148	135	118	101	81	59																1¼	8.8	
S4P-1E/26	1.1		177	156	143	127	109	89	68																1¼	9	
S4P-1E/33	1.5		220	199	179	160	136	112	88																1¼	11.6	
S4P-1E/34	1.5		226	202	188	172	149	124	98															1¼	12		
S4P-2/05	0.37	Head in meters	44		40	39	38	35	31	25	13														1¼	2.8	
S4P-2/07	0.55		62		59	56	52	49	45	34	22														1¼	3.1	
S4P-2/11	0.75		98		90	87	82	77	70	53	35														1¼	3.8	
S4P-2/16	1.1		143		131	127	119	112	100	78	48														1¼	6.5	
S4P-2/22	1.5		194		172	165	153	142	129	100	65														1¼	7.7	
S4P-2/30	2.2		260		232	223	209	192	172	135	92														1¼	10.5	
S4P-3/07	0.55	Head in meters	52						42	38	33	26	18	2											1¼	2.8	
S4P-3/08	0.55		59						52	45	39	31	22	4											1¼	3.4	
S4P-3/11	0.75		80						70	62	54	45	34	8											1¼	3.9	
S4P-3/15	1.1		111						98	88	77	63	48	12											1¼	4.9	
S4P-3/20	1.5		150						128	116	101	82	61	13											1¼	7.9	
S4P-3/21	1.5		157						133	121	107	86	63	15											1¼	8.2	
S4P-3/28	2.2		208						177	161	141	115	88	22											1¼	10.9	
S4P-3/30	2.2			221					190	172	151	125	96	26											1¼	11.7	
S4P-4/05	0.55	Head in meters	38						32	31	28	26	22	15	8										1¼	1.9	
S4P-4/06	0.55		46						40	38	37	34	31	21	12										1¼	2.4	
S4P-4/07	0.75		54						49	47	44	41	37	25	14										1¼	3.3	
S4P-4/10	1.1		79						69	66	62	57	51	39	22										1¼	4	
S4P-4/11	1.1		86						77	77	72	67	61	47	29										1¼	4.4	
S4P-4/14	1.5		110						99	85	89	82	73	55	35										1¼	5.6	
S4P-4/15	1.5		118						108	102	96	88	79	60	38										1¼	6	
S4P-4/20	2.2		158						141	135	128	119	110	82	49										1¼	8	
S4P-4/22	2.2		185						165	156	148	138	128	98	58										1¼	8.8	
S4P-4/27	3		210						198	182	183	172	159	120	71										1¼	10.8	
S4P-4/35	3.7		270					248	237	228	210	192	140	81										1¼	14		
S4P-5/06	0.75	Head in meters	42								39	37	37	32	27	18	9								1¼	3.4	
S4P-5/08	1.1		58								53	52	49	42	34	25	15								1¼	2.3	
S4P-5/09	1.1		65								59	57	55	50	41	31	17								1¼	3	
S4P-5/11	1.5		79								72	69	67	58	48	35	20								1¼	3.5	
S4P-5/12	1.5		86								78	76	73	65	55	42	25								1¼	4.3	
S4P-5/17	2.2		123								115	110	105	91	76	57	31								1¼	4.8	
S4P-5/21	3		145								135	121	126	111	92	70	39								1¼	6.6	
S4P-5/27	3.7		184							163	157	158	138	116	80	42								1¼	8.2		
S4P-8/04	0.75	Head in meters	25										21	22	20	20	19	14	8						2	3.8	
S4P-8/06	1.1		38										35	34	32	31	28	22	13						2	4.4	
S4P-8/08	1.5		51										48	47	45	43	40	31	20						2	3.2	
S4P-8/13	2.2		82										72	71	69	65	61	48	29						2	6.5	
S4P-8/17	3		108										101	99	96	91	85	69	43						2	7.9	
S4P-8/23	4		143										132	128	122	116	109	88	52						2	10	
S4P-8/32	5.5		200										182	175	168	159	148	116	68						2	13	
S4P-8/43	7.5		270										242	233	221	210	193	149	88					2	17.5		
S4P-10/03	0.75	Head in meters	17										16	16	15	14	14	12	9	5					2	2.72	
S4P-10/04	0.75		22										21	21	20	19	18	16	13	7					2	3	
S4P-10/05	1.1		27										26	26	25	24	23	20	16	9					2	4.3	
S4P-10/06	1.1		34										33	32	31	30	28	24	19	12					2	5.1	
S4P-10/07	1.5		39										37	37	35	34	33	28	22	14					2	5.5	
S4P-10/08	1.5		46										43	43	42	40	38	33	27	12					2	6	
S4P-10/10	2.2		57										54	53	52.5	50	48	42	33	22					2	7.6	
S4P-10/12	2.2		66										64	64	62.5	60	57	50	39	25					2	9.1	
S4P-10/15	3		83										78	77	75	73	69	61	48	33					2	11.3	
S4P-10/17	3		94										88	87	84	82	78	69	55	39					2	11.8	
S4P-10																											